








ZESTAWIENIE STOLARKI DRZWIOWEJ DLA PARTERU

OZNACZENIE									
SCHEMAT									
Wymiary otworu w ścianie	So	1350	1050	1000	1000	900	1000	1000	
	Ho	2100	2100	2050	2050	2050	2050	2050	
Wymiary w świetle ościeżnicy	Sz	900+300	900	900	900	800	900	900	
	Hz	2000	2000	2000	2000	2000	2000	2000	
Ilość sztuk	Piwnica	L							
		P							
	Parter	L	1	0	4	2	2	1	0
		P	0	1	3	3	0	1	1
	Piętro	L							
		P							
Ilość sztuk razem		0P / 1L	1P / 0L	3P / 4L	3P / 2L	0P / 2L	1P / 1L	1P / 0L	
Ilość sztuk ogółem		1	1	7	5	2	2	1	
Uwagi		PCV ZEWNĘTRZNE Z SAMOZAMYKACZEM Uc = 1,1 W/m2K	PCV ZEWNĘTRZNE Z SAMOZAMYKACZEM Uc = 1,1 W/m2K	PŁYGINOWE	PŁYGINOWE Z SAMOZAMYKACZEM ŁAZIENKOWE	PŁYGINOWE ŁAZIENKOWE	STALOWE EI 30	STALOWE EI 60	